



# Xiangtan Huaxing Material Co., Ltd.



5.118 Inch | 130 Millimeter x 11.024 Inch | 280 Millimeter x 2.283 Inch | 58 Millimeter NTN TS2-NU326CL1BCS186 Cylindrical Roller Bearings

Bearing No. TS2-NU326CL1BCS186

TS2-NU326CL1BCS186 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	15.48
EAN	4547359500233
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Plain Inner Ring   2 Rib Outer Ring   Heat Stabilization Up to 160 Deg C   Cage on Outer Ring ID
Long Description	130MM Bore; Straight Bore



## Xiangtan Huaxing Material Co., Ltd.

	Profile; 280MM Outside Diameter; 58MM Width; Brass Cage Material; RBEC 1   ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	TS2-NU326CL1BCS186
Weight / LBS	34.1
D	11.024 Inch   280 Millimeter
B	2.283 Inch   58 Millimeter
d	5.118 Inch   130 Millimeter
bore diameter:	130 mm
static load capacity:	665000 N
outside diameter:	280 mm
precision rating:	ISO Class 0
overall width:	58 mm
bearing material:	Hardened Alloy Steel
flanges:	(2) Outer Ring
cage material:	High Strength, 2 piece, Machined Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	Special Clearance
fillet radius:	3 mm
ring separation:	Separable Inner Ring



## Xiangtan Huaxing Material Co., Ltd.

series:	TS2
operating temperature range:	-40 to 120 ° C
manufacturer product page:	<a href="#">Click here</a>
dynamic load capacity:	560000 N