



Xiangtan Huaxing Material Co., Ltd.



2.938 Inch | 74.625 Millimeter x 6.75 Inch |
 171.45 Millimeter x 4.5 Inch | 114.3 Millimeter SKF
 SAF 22617 Pillow Block Bearings

Bearing No. SAF 22617

SAF 22617 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	34.05
EAN	7316576669422
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Tapered Adapter Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	7/8 Inch
Relubricatable	Yes
Insert Part Number	22317 CCK/W33
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch - Metric	Inch
Other Features	Double Row Heavy Duty
Long Description	2 Bolt Pillow Block; 2-15/16" Bore; 4-1/2" Base to Center Height; Tapered Adapter Sleeve Mount; Spherical Roller Bearing; 11-5/8" Minimum Bolt



Xiangtan Huaxing Material Co., Ltd.

	Spacing; 13-1/8" Bolt Spacing Maximum
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SAF 22617
Weight / LBS	75
d	2.938 Inch 74.625 Millimeter
B	4.5 Inch 114.3 Millimeter
D	6.75 Inch 171.45 Millimeter
Bolt Spacing Maximum	13.125 Inch 333.375Millimeter
Nominal Bolt Center to Center	12.4 Inch 315 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Minimum	11.625 Inch 295.275Millimeter
d _a	74.612 mm
D _a	180 mm
C _a	69.799 mm
A ₁	111.125 mm
A ₂	173.037 mm
S	4.763 mm
b _a	48.419 mm
H	222.25 mm
H ₁	114.3 mm
H ₂	44.45 mm
J min.	295.275 mm



Xiangtan Huaxing Material Co., Ltd.

J max.	333.375 mm
L	387.35 mm
N ₁	25.4 mm
R ₁	66.675 mm
R ₂	30.163 mm
R _G	3/8 NPT
P _G	1/8 NPT
h	44.45 mm
Housing	SAF 617
Bearing	22317 EK
Adapter sleeve assembly	SNW 117x2.15/16
Stabilizing ring	SR-20-17
Labyrinth ring	2 x LOR 184
End plug (suffix Y)	EPR 10
Bearing limiting speed	3800 r/min
P _{60°}	94.3 kN
P _{90°}	56.5 kN
P _{120°}	35.6 kN
P _{150°}	32 kN
P _{180°}	38.3 kN
P _a	15.3 kN
Mass pillow block	33.9 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g